

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>1/6</b>
No. 00373	EN 1856-1:2009	UE_DoP_00373_EN_M	

1. Unique identification code of the product-type:  
**Twin walled stainless steel system with air gap - Metaloterm® UE according to EN 1856-1:2009**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):
  - Model 1 DN (ø80–250) EN 1856-1 T200 P1 W V2 L50040 O25
  - Model 2 DN (ø80–250) EN 1856-1 T200 H1 W V2 L50040 O25
  - Model 3 DN (ø80–250) EN 1856-1 T250 N1 W V2 L50040 O25
  - Model 4 DN (ø80–250) EN 1856-1 T400 N1 W V2 L50040 O130
  - Model 5 DN (ø80–250) EN 1856-1 T400 N1 D V3 L50040 G130
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
Convey the products of combustion from heating appliances to the outside atmosphere
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):  
Schiedel Metaloterm B.V.  
Oude Veerseweg 23, 4332 SH Middelburg  
The Netherlands  
T: +31 (0)118 68 99 00  
F: +31 (0)118 68 99 99  
E: info.nl@metaloterm.com
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  
System 2+ and System 4
7. Notified factory production control certification body No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity **0432-CPR-00373-60** of the factory production control.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
Not applicable

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>2/6</b>
No. 00373	EN 1856-1:2009	UE_DoP_00373_EN_M	

9. Declared performance

	Essential Characteristics	Performance	Harmonized technical specification
9.1	Compressive strength Chimney sections, fittings and supports	Sections and fittings: Model 1 to 5 DN (80-250): up to 50 m For further information see <a href="http://www.metaloterm.com">www.metaloterm.com</a>	EN 1856-1:2009
9.2	Resistance to fire	(Resistance to fire from inside to outside) Model 1 DN (80-250): T200 – O25 Model 2 DN (80-250): T200 – O25 Model 3 DN (80-250): T250 – O25 Model 4 DN (80-250): T400 – O130 Model 5 DN (80-250): T400 – G130 Tested without cover, with back ventilated ceiling duct	EN 1856-1:2009
9.3	Gas tightness/leakage	Model 1 DN (80-250): P1 Model 2 DN (80-250): H1 Model 3 DN (80-250): N1 Model 4 DN (80-250): N1 Model 5 DN (80-250): N1	EN 1856-1:2009
9.4	Flow resistance of chimney sections fittings and terminals	According to EN 13384-1	EN 1856-1:2009
9.5	Thermal resistance	Model 1 to 5 DN (80-250): 0,15 m <sup>2</sup> K/W tested at 200°C	EN 1856-1:2009
	Thermal shock resistance		
9.6	Sootfire resistance	Model 1 DN (80-250): No* Model 2 DN (80-250): No* Model 3 DN (80-250): No* Model 4 DN (80-250): No* Model 5 DN (80-250): Yes * because designated O	EN 1856-1:2009
9.7	Thermal performance under normal operating conditions	Model 1 DN (80-250): T200 Model 2 DN (80-250): T200 Model 3 DN (80-250): T250 Model 4 DN (80-250): T400 Model 5 DN (80-250): T400	EN 1856-1:2009
9.8	Flexural tensile strength (only for means of connection for chimney sections and fittings)	Model 1 to 5 DN (80-250): up to 0 m	EN 1856-1:2009
9.9	Non vertical installation	Model 1 to 5 DN (80-250): Maximum offset between supports 1.5 m at 90° (inclined run, maximum distance between two fixations, supports at non vertical installation)	EN 1856-1:2009
9.10	Components subject to wind load	Model 1 to 5 DN (80- 250): Free standing height 2.5 m above last support Maximum spacing between lateral supports: 2 m	EN 1856-1:2009
	Durability:		
9.11	Water and vapour diffusion resistance	Yes if W	EN 1856-1:2009
9.12	Condensate penetration resistance	Model 1 DN (80-250): Yes Model 2 DN (80-250): Yes Model 3 DN (80-250): Yes Model 4 DN (80-250): Yes Model 5 DN (80-250): No	EN 1856-1:2009

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>3/6</b>
No. 00373	EN 1856-1:2009	UE_DoP_00373_EN_M	

	Essential Characteristics	Performance	Harmonized technical specification
9.13	Against corrosion	Model 1 DN (80-250): V2 Model 2 DN (80-250): V2 Model 3 DN (80-250): V2 Model 4 DN (80-250): V2 Model 5 DN (80-250): V3	EN 1856-1:2009
9.14	Freeze thaw resistance	Model 1 to 5 DN (80-250): Yes	EN 1856-1:2009

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Middelburg, 2020-01-01

Simon Ramaekers  
CEO Schiedel Benelux

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>4/6</b>
No. 00373	EN 1856-2:2009	UE_DoP_00373_EN_M	

1. Unique identification code of the product-type:  
**Twin walled stainless steel system with air gap - Metaloterm® UE according to EN 1856-2:2009**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):
  - Model 1 DN (ø80–250) EN 1856-2 T200 P1 W V2 L50040 O50
  - Model 2 DN (ø80–250) EN 1856-2 T200 H1 W V2 L50040 O50
  - Model 3 DN (ø80–250) EN 1856-2 T400 N1 W V2 L50040 O200
  - Model 4 DN (ø80–250) EN 1856-2 T400 N1 D V3 L50040 G200
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
Convey the products of combustion from heating appliances to the chimney
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):  
Schiedel Metaloterm B.V.  
Oude Veerseweg 23, 4332 SH Middelburg  
The Netherlands  
T: +31 (0)118 68 99 00  
F: +31 (0)118 68 99 99  
E: info.nl@metaloterm.com
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:  
System 2+ and System 4
7. Notified factory production control certification body No. 0432 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity **0432-CPR-00373-61** of the factory production control.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
Not applicable

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>5/6</b>
No. 00373	EN 1856-2:2009	UE_DoP_00373_EN_M	

9. Declared performance

	Essential Characteristics	Performance	Harmonized technical specification
9.1	Compressive strength Chimney sections, fittings and supports	Sections and fittings: Model 1 to 4 DN (80-250): up to 50 m For further information see <a href="http://www.metaloterm.com">www.metaloterm.com</a>	EN 1856-2:2009
9.2	Resistance to fire	(Resistance to fire from inside to outside) Model 1 DN (80-250): T200 – O50 Model 2 DN (80-250): T200 – O50 Model 3 DN (80-250): T400 – O200 Model 4 DN (80-250): T400 – G200 Tested without cover, with back ventilated ceiling duct	EN 1856-2:2009
9.3	Gas tightness/leakage	Model 1 DN (80-250): P1 Model 2 DN (80-250): H1 Model 3 DN (80-250): N1 Model 4 DN (80-250): N1	EN 1856-2:2009
9.4	Flow resistance of chimney sections fittings and terminals	According to EN 13384-1	EN 1856-2:2009
9.5	Thermal resistance	Model 1 to 4 DN (80-250): 0,15 m <sup>2</sup> K/W tested at 200°C	EN 1856-2:2009
	Thermal shock resistance		
9.6	Sootfire resistance	Model 1 DN (80-250): No* Model 2 DN (80-250): No* Model 3 DN (80-250): No* Model 4 DN (80-250): Yes * because designated O	EN 1856-2:2009
9.7	Thermal performance under normal operating conditions	Model 1 DN (80-250): T200 Model 2 DN (80-250): T200 Model 3 DN (80-250): T400 Model 4 DN (80-250): T400	EN 1856-2:2009
9.8	Flexural tensile strength (only for means of connection for chimney sections and fittings)	Model 1 to 4 DN (80-250): up to 0 m	EN 1856-2:2009
9.9	Non vertical installation	Model 1 to 4 DN (80-250): Maximum offset between supports 1.5 m at 90° (inclined run, maximum distance between two fixations, supports at non vertical installation)	EN 1856-2:2009
9.10	Components subject to wind load	Model 1 to 4 DN (80- 250): Free standing height 2.5 m above last support Maximum spacing between lateral supports: 2 m	EN 1856-2:2009
	Durability:		
9.11	Water and vapour diffusion resistance	Yes if W	EN 1856-2:2009
9.12	Condensate penetration resistance	Model 1 DN (80-250): Yes Model 2 DN (80-250): Yes Model 3 DN (80-250): Yes Model 4 DN (80-250): No	EN 1856-2:2009

<b>Declaration of Performance</b>	<b>Metaloterm® UE</b>	<b>EN</b>	<b>6/6</b>
No. 00373	EN 1856-2:2009	UE_DoP_00373_EN_M	

	Essential Characteristics	Performance	Harmonized technical specification
9.13	Against corrosion	Model 1 DN (80-250): V2 Model 2 DN (80-250): V2 Model 3 DN (80-250): V2 Model 4 DN (80-250): V3	EN 1856-2:2009
9.14	Freeze thaw resistance	Model 1 to 4 DN (80-250): Yes	EN 1856-2:2009

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Middelburg, 2020-01-01

Simon Ramaekers  
CEO Schiedel Benelux