



# **CERTIFICATE**



#### 0036 CPD 9195 030 Revision 02

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21st December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD) amended by the Directive 93/68/EEC of the Council of European Communities of 22<sup>nd</sup> July 1993, it has been stated that the construction product

### **System Chimney Permeter Smooth** models

| modelo           |           |                          |
|------------------|-----------|--------------------------|
| model 1, -2, -3  | EN 1856-1 | T450 N1 D V2 L50050 GXX  |
| model 4          | EN 1856-1 | T400 N1 D V2 L50050 G25  |
| model 5, -6, -7, | EN 1856-1 | T450 N1 D V2 L99050 GXX  |
| model 8          | FN 1856-1 | T400 N1 D V2 1 99050 G25 |

GXX model G25 model 8 EN 1856-1 T450 N1 D Vm L20050 GXX model 9, -10, -11 model 12 EN 1856-1 T400 N1 D Vm L20050 G25 T450 N1 D V3 L50050 GXX model 13, -14 EN 1856-1

T450 N1 D V3 L50050 G25 model 15 EN 1856-1 1) for details of designation see second page of certificate

produced by

## Schiedel Chimney Systems Ltd. **Crowther Estate** Washington, Tyne & Wear, NE38 0AQ (GB)

in the factory

Schiedel Chimney Systems Ltd. Washington, Tyne & Wear, NE38 0AQ (GB)

is submitted to

- the initial type testing, performed by TÜV SÜD Industrie Service GmbH, test reports A 1911-00/11 as well as
- a factory production control

The Notified Body TÜV SÜD Industrie Service GmbH has performed the initial inspection of the factory and the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of factory production control described in Annex ZA of the standard

EN 1856-1: 2009-06

were applied.

This certificate was first issued on 2007-06-06 and - with respect to the conditions of the certification contract - remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Munich, 2012-04-16

J. Steiglechner

#### 0036 CPD 9195 030 Revision 02



| Permeter Smooth             | EN 1856-1                |
|-----------------------------|--------------------------|
| model 1<br>DN 130 – DN 200  | T450 N1 D V2 L50050 G60  |
| model 2<br>DN 130 – DN 200  | T450 N1 D V2 L50050 G50  |
| model 3<br>DN 130 – DN 200  | T450 N1 D V2 L50050 G25* |
| model 4<br>DN 130 – DN 200  | T400 N1 D V2 L50050 G25* |
| model 5<br>DN 130 – DN 200  | T450 N1 D V2 L99050 G60  |
| model 6<br>DN 130 – DN 200  | T450 N1 D V2 L99050 G50  |
| model 7<br>DN 130 – DN 200  | T450 N1 D V2 L99050 G25* |
| model 8<br>DN 130 – DN 200  | T400 N1 D V2 L99050 G25* |
| model 9<br>DN 130 – DN 200  | T450 N1 D Vm L20050 G60  |
| model 10<br>DN 130 – DN 200 | T450 N1 D Vm L20050 G50  |
| model 11<br>DN 130 – DN 200 | T450 N1 D Vm L20050 G25* |
| model 12<br>DN 130 – DN 200 | T400 N1 D Vm L20050 G25* |
| model 13<br>DN 130 – DN 200 | T450 N1 D V3 L20050 G60  |
| model 14<br>DN 130 – DN 200 | T450 N1 D V3 L20050 G50  |
| model 15<br>DN 130 – DN 200 | T450 N1 D V3 L20050 G25* |

<sup>\* = 50</sup> mm insulation